



No. 1703-AS Center-Take-Off Pulley

Suspended Mount

1 – 3 lbs. 5 oz.

Center-Take-Off Pulley for suspended track systems. Designed to route the operating lines perpendicular to the track. Must add 1 each 1704 Dead End pulley if used. 1703-AS must be located a minimum of 4' from the end of the track. Additional pulleys may be required to mule operating lines to floor pulley or machine. Approximately: 4-1/2" long x 4-7/8" wide x 3-13/16" high.



No. 1724 (BL) Splicing Clamp

1 pr. - 4 lbs. 3 oz.

Two piece 11 gauge steel clamp for joining track sections assuring proper alignment of channels.

Approximately: 12" long x 2" wide x 3-3/4" high.

NOTE: For suspended tracks only.



No. 1708 (BL) Hanging Clamp

1 pr. - 6.5 oz.

Recommended spacing: 6'. Steel, chain or cable suggested for track suspension. Adjustable to any location.



No. 2624 (BL) Splicing Clamp

1 pr. - 2 lbs.

Two piece 11 gauge steel clamp for joining track sections on ceiling-mounted installations assuring proper alignment of channels.

Approximately: 12" long x 2" wide x 2-1/4" high.

NOTE: For ceiling mounted systems only.



No. 1709 (BL) End Stop

1 - 4.5 oz.

Prevents carriers from moving beyond selected position in track.

Cannot be used with Rotodrapers®. Proper hardware supplied with Rotodrapers®.



No. 1707 (BL) Lap Clamp

1 - 9.5 oz.

For securing bi-parting tracks at center overlap. For suspended tracks only. Sold individually.



No. CPS-2 Center Pipe Support

1 pr - 5.5 oz.

To facilitate the clamping of steel track channel to pipe batten, a Center Pipe Support is available. The Center Pipe Support is placed at the overlap, and the two lap clamps are used in the normal manner.

Lap & pipe clamps sold separately.



No. 2865 (BL) Tension Floor Pulley

1 - 1 lb. 12 oz.

Plated steel construction equipped with 1 oil-impregnated sleeve-bearing nylon wheel. Tension spring provides cord tension. Can be either wall or floor mounted. Spring-loaded latch maintains wheel in uppermost position during installation. Approximately: 1-1/2" long x 3-1/2" wide x 13" high.



No. 2805 (BL) Adjustable Floor Pulley

1 - 4 lbs. 5 oz.

Powder Coated steel side plates equipped with 1 oil-impregnated sleeve-bearing wheel. Locks in place via threaded axle. Adjustment – 9".

Approximately: 3-1/4" long x 5" wide x 13" high.