



SPECIFICATIONS:

SILENT STEEL® Model 280 [380] Curtain Tracks

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2801(BL)**) shall be spaced on 12" centers and shall be of nylon construction supported from a ball-bearing by two polyethylene wheels held to ball-bearing by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. Live-End pulley (**Model 2803(BL)**) and Dead-End pulleys (**Model 2804(BL)**) shall be adjustable and shall be equipped with 3" diameter sleeve-bearing wheels adequately guarded. A rubber bumper shall be attached to each curtain carrier to function as noise reducer. The manufacturer shall furnish two End Stops (**Model 2809(BL)**) for placement at each track end and a tension Floor Pulley (**Model 2865(BL)**) for increasing cord tension. Stretch-resistant operating cord (Model 2828 for hand operation and Model 3529 for machine operation) shall have synthetic or wire center and shall be of 3/8" or 3/16" diameter. If Back Pack® devices are used with this track, **Model 2833** is used for hand operated track systems and **Model 2834** is used for machine operated track systems. Model 280(380) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 281 [381] Curtain Tracks

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2849(BL)**) shall be spaced on 12" centers and shall be of steel construction with two neoprene-tired ball-bearing wheels held to steel body by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. Live-End pulleys (**Model 2803(BL)**) and Dead-End pulley (**Model 2804(BL)**) shall be adjustable and shall be equipped with 3" diameter sleeve-bearing wheels adequately guarded. A rubber washer shall be attached to each curtain carrier to function as noise reducer. The manufacturer shall furnish two End Stops for placement at each track end and a tension Floor Pulley (**Model 2865(BL)**) for increasing cord tension. Stretch-resistant operating cord (Model 2828 for hand operation and Model 3529 for machine operation) shall have synthetic or wire center and shall be of 3/8" or 3/16" diameter. If Back Pack® devices are used with this track, **Model 2833** is used for hand operated track systems and **Model 2834** is used for machine operated track systems. Model 281(381) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 282 [382] Curtain Tracks

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2851(BL)**) shall be spaced on 12" centers and shall be of steel construction with two nylon-tired ball-bearing wheels held to steel body by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. Live-End pulley (**Model 2863(BL)**) and Dead-End pulleys (**Model 2864(BL)**) shall be adjustable and shall be equipped with 5" diameter sleeve-bearing wheels adequately guarded. A rubber bumper shall be attached to each curtain carrier to function as noise reducer. The manufacturer shall furnish two End Stops for placement at each track end and a tension Floor Pulley (**Model 2866**) for increasing cord tension. Stretch-resistant operating cord (Model 2828 for hand operation and Model 3529 for machine operation) shall have synthetic or wire center and shall be of 3/8" or 3/16" diameter. If Back Pack® devices are used with this track, **Model 2833** is used for hand operated track systems and **Model 2834(BL)** is used for machine operated track systems. Model 282(382) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 280-A [380-A] Curtain Tracks

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2801-B(BL)**) shall be spaced on 12" centers and shall be steel construction with two polyethylene wheels held to the steel body by a rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. Live-End pulley (**Model 2803(BL)**) and Dead-End pulleys (**Model 2804(BL)**) shall be adjustable and shall be equipped with 3" diameter sleeve-bearing wheels adequately guarded. A rubber bumper shall be attached to each curtain carrier to function as noise reducer. The manufacturer shall furnish two End Stops (**Model 2809(BL)**) for placement at each track end and a tension Floor Pulley (**Model 2865(BL)**) for increasing cord tension. Stretch-resistant operating cord (Model 2828 for hand operation and Model 3529 for machine operation) shall have synthetic or wire center and shall be of 3/8" or 3/16" diameter. If Back Pack® devices are used with this track, **Model 2833(BL)** is used for hand operated track systems and **Model 2834(BL)** is used for machine operated track systems. Model 280-A(380-A) as manufactured by Automatic Devices Company of Allentown, PA.