

SPECIFICATIONS:

SILENT STEEL® Model 283-N [383-N] Curtain Tracks

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2851(BL)**) shall be spaced on 12" centers and shall be of steel construction with two nylon-tired ball-bearing wheels held to steel body by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. Live-End pulley (**Model 2863-A(BL)**) and Dead-End pulleys (**Model 2864-A(BL)**) shall be adjustable and shall be equipped with 8" diameter ball-bearing wheels adequately guarded. A rubber washer shall be attached to each curtain carrier to function as noise reducer. The manufacturer shall furnish two End Stops (**Model 2809(BL)**) for placement at each track end and a tension Floor Pulley (**Model 2866-A(BL)**) for increasing and decreasing cord tension. Stretch-resistant operating cord (Model 2830 for hand operation and Model 3529 for machine operation) shall have synthetic or wire center and shall be of 1/2", or 3/16" diameter. If Back Pack® devices are used with this track, **Model 2833-A(BL)** is used for hand operated track systems and **Model 2834(BL)** is used for machine operated track systems.

Model 283-N (383-N) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 283-R [383-R] Curtain Tracks

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2849(BL)**) shall be spaced on 12" centers and shall be of steel construction with two neoprene-tired ball-bearing wheels held to steel body by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. Live-End pulley (**Model 2863-A(BL)**) and Dead-End pulleys (**Model 2864-A(BL)**) shall be adjustable and shall be equipped with 8" diameter ball-bearing wheels adequately guarded. A rubber washer shall be used between each curtain carrier to function as noise reducer. The manufacturer shall furnish two End Stops (**Model 2809(BL)**) for placement at each track end and a tension Floor Pulley (**Model 2866-A(BL)**) for increasing and decreasing cord tension. Stretch-resistant operating cord (Model 2830 for hand operation and Model 3529 for machine operation) shall have synthetic or wire center and shall be of 1/2", or 3/16" diameter. If Back Pack® devices are used with this track, **Model 2833-A(BL)** is used for hand operated track systems and **Model 2834(BL)** is used for machine operated track systems.

Model 283-R (383-R) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 284 [384] Curtain Tracks [Walk-Along Track System]

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2801(BL)**) shall be spaced on 12" centers and shall be of nylon construction supported from a ball-bearing by two polyethylene wheels held to ball-bearing by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. A rubber washer shall be attached to each curtain carrier to function as noise reducer. The manufacturer shall furnish four End Stops (**Model 2809(BL)**) for placement at each track end. This model track system is for walk-along operation only and does not include pulleys or other operating hardware.

Model 284 (384) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 284-N [384-N] Curtain Tracks [Walk-Along Track System]

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2851(BL)**) shall be spaced on 12" centers and shall be of steel construction supported from a ball-bearing by two nylon-tired ball-bearing wheels held to carrier body by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. The manufacturer shall furnish four End Stops (**Model 2809(BL)**) for placement at each track end. This model track system is for walk-along operation only and does not include pulleys or other operating hardware.

Model 284-N (384-N) as manufactured by Automatic Devices Company of Allentown, PA.

SILENT STEEL® Model 284-R [384-R] Curtain Tracks [Walk-Along Track System]

Curtain tracks Model 2800 (2800A) shall be of 14 gauge galvanized steel construction (2800A - 12 Gauge aluminum), entirely enclosed except for slot in bottom, each half to be in one continuous piece except where splicing clamps are required. Each curtain carrier (**Model 2849(BL)**) shall be spaced on 12" centers and shall be of steel construction supported from a ball-bearing by two neoprene-tired ball-bearing wheels held to carrier body by rustproof nickel plated rivet, such wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel and sufficient trim chain to accommodate curtain snap hook. The manufacturer shall furnish four End Stops (**Model 2809(BL)**) for placement at each track end. This model track system is for walk-along operation only and does not include pulleys or other operating hardware.

Model 284-R (384-R) as manufactured by Automatic Devices Company of Allentown, PA.