



TRIPL-I-TRAC® 420 SERIES CURTAIN TRACKS

420

		420 TRIPL-I-TRAC® CWANA code					
		CORD OPERATED/MOTORIZED				WALK-ALONG	
Parts Included		420	420-R	421	421-R	422	422-R
STRAIGHT				√	√		
CURVED		√	√			√	√
Single Carriers	4201	√		√		√	
	4237		√		√		√
Master Carriers	4252			√		√	
	4253		√		√		√
Pulleys	4202	√	√				
	4203	√	√				
	4204	√	√				
Spindles & Idlers	2865	√	√				
	4258	√	√				
	4259	√	√				
Cord	4260	√	√				
	1728	√	√				

*FOR MACHINE OPERATED TRACK SYSTEMS, REPLACE 1728 CORD WITH 3529 CABLE. DELETE THE 2865 FLOOR PULLEY.

SPECIFICATIONS:

TRIPL-I-TRAC® Model 420 Curtain Tracks

Curtain tracks (Model 4200) shall be of 7 gauge extruded aluminum I-beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4201**) shall be spaced on 12" centers and shall be of steel construction to include two nylon-tired ball-bearing wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Live-End (**Model 4203**) and Dead-End (**Model 4204**) pulley blocks shall be equipped with sleeve-bearing wheels adequately guarded. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. The manufacturer shall furnish two End Stops (**Model 4209**) for placement at track ends and a tension Floor Pulley (**Model 2865**) for increasing cord tension. Track shall be rigidly supported from Ceiling Clamps (**Model 4223**) or Hanging Clamps (**Model 4208**). Stretch-resistant operating cord (Model 1728 for hand operating tracks and Model 3529 for machine operated tracks) shall have synthetic or wire center and shall be of 1/4" or 3/16" diameter. Curves require ball-bearing Spindles (**Models 4258 & 4259**) and ball-bearing Idlers (**Model 4260**). 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support both straight and curved areas of all suspended curved tracks. Model 420 as manufactured by Automatic Devices Company of Allentown, PA.

TRIPL-I-TRAC® Model 420-R Curtain Tracks

Curtain tracks (Model 4200) shall be of 7 gauge extruded aluminum I-beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4237**) shall be spaced on 12" centers and shall be of steel construction to include two solid nylon wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Live-End (**Model 4203**) and Dead-End (**Model 4204**) pulley blocks shall be equipped with sleeve-bearing wheels adequately guarded. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. The manufacturer shall furnish two End Stops (**Model 4209**) for placement at track ends and a tension Floor Pulley (**Model 2865**) for increasing cord tension. Track shall be rigidly supported from ceiling clamps (**Model 4223**) or Hanging Clamps (**Model 4208**). Stretch-resistant operating cord (Model 1728 for hand operating tracks and Model 3529 for machine operated tracks) shall have synthetic or wire center and shall be of 1/4" or 3/16" diameter. Curves require ball-bearing Spindles (**Models 4258 & 4259**) and ball-bearing Idlers (**Model 4260**). 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support both straight and curved areas of all suspended curved tracks. Model 420-R as manufactured by Automatic Devices Company of Allentown, PA.