



Full Size End View



No. 4200 (BL) Channel

1' - 1 lb. 8 oz.
7 gauge extruded aluminum, mill-finish (4200BL anodized black). Obtainable in unspliced lengths up to 20'. Curved on-the-job or at the factory (optional) to a 2' minimum radius (layout dependent). Flange above carrier prevents tilting of carrier.
Approximately: 1" wide x 3-3/8" high.



No. 4201 (BL) Single Carrier

1 - 4 oz.
Carrier spacing: 12". Plated steel block supported from 2 nylon-tired ball-bearing wheels. Snap-on nylon spacers reduce noise and friction.
Width: Approximately 1-3/8".



No. 1402 (BL) Master Carrier

1 - 11 oz.
Used with Model 420 track systems. Plated steel pivoting block assembly supported from 4 nylon-tired ball-bearing wheels. Snap-on nylon spacers reduce noise and friction. 2 cord connectors provided for clamping operating cord to carrier assembly.
Width: Approximately 4".



No. 4237 Single Carrier

1 - 3 oz.
Carrier spacing: 12". Plated steel block supported from 2 solid nylon wheels. Snap-on nylon spacers reduce noise and friction.
Width: Approximately 1-3/8".



No. 4252 (BL) Walk-Along Master Carrier

1 - 8.5 oz.
Used with Models 422 and 142 tracks. Plated steel pivoting block assembly supported from 4 nylon-tired ball-bearing wheels. Snap-on nylon spacers reduce noise and friction.
Width: Approximately 3".