



TRIPL-I-TRAC® 420 SERIES CURTAIN TRACKS

420



No. 4253 (BL) Walk-Along Master Carrier

1 – 7 oz.
Used with Models 422-R and 142-R tracks. Plated steel pivoting block assembly supported from 4 solid nylon wheels. Snap-on nylon spacers reduce noise and friction.
Width: Approximately 3".



No. 4204 Dead End Pulley

1 – 1 lb. 4 oz.
Painted steel construction equipped with 1 oil-impregnated sleeve-bearing nylon wheel. Attaches to the end of the 4200 track.
Pulley width: Approximately 5-1/4".



No. 1423 (BL) Ceiling Clamp

1 – 6 oz.
Used to attach track directly to overhead structure. Recommended spacing 5' with additional units in curve and stack areas.
Approximately: 3-1/4" wide x 1-1/2" long x 3/16" high



No. 4203 Live End Pulley

1 – 1 lb. 15 oz.
Equipped with 2 oil-impregnated sleeve-bearing nylon wheels. Attaches to the end of the 4200 track.
Pulley width: Approximately 7".



No. 4224 (BL) Splicing Clamp

1 pr. - 12 oz.
Lock plate for joining track sections assuring proper vertical and horizontal track alignment.
Approximately: 8-1/4" long x 1" wide.
NOTE: Track must be straight at splices.



No. 4209 (BL) End Stop

1 pr. - 2-1/2 oz.
Identical to No. 4208 except installed in inverted position at bottom of channel. Prevents carriers from moving beyond selected position in track.



No. 4203-B Live End Pulley

1 - 2 lbs. 4 oz.
Used with straight track systems only. (Models 421 and 421-R). Painted steel construction with 2 oil-impregnated sleeve bearing nylon wheels.
Pulley width: Approximately 3-1/4".



No. 4208 (BL) Hanging Clamp

1 pr. - 2-1/2 oz.
Recommended spacing: 4' with additional units in curve and stack areas. Pipe batten recommended for suspended curved tracks.
Plated steel construction.
Approximately: 1-1/4" wide x 1-3/16" long x 2-1/8" high.



No. 4260-A (BL) Idler

1 – 10 oz.
Used at the overlap of continuously curved bi-parting systems to prevent cord from rubbing against end of tracks.

Cannot be used with Rotodrapers®. Proper hardware is supplied with Rotodrapers®.