



**No. 5002-S Master Carrier With Extension Arm**

1 - 4 lbs. 12 oz.

Used with single section track systems to create center overlap. Creates 20" overlap (10" in front of 10").

Approximately: 1'-4" long x 6-9/16" high x 3-3/4" wide.



**No. 5002-A Walk-Along Master Carrier**

1 - 1 lb. 13 oz.

Master carrier for Model 500 track series systems with walk-along operation. Painted steel construction with nylon-tired ball-bearing equipped wheels and rubber bumpers for noise suppression.

Approximately: 5-1/16"L x 2-3/16"W



**No. 5051 Scenery Panel Carrier**

1 - 2 lbs. 6 oz.

Walk-along panel carrier for Model 500 track series systems. Adjustable bottom plate mounts directly to the top of the scenery panel allowing for leveling of the panel after installation. Painted steel construction with nylon-tired ball-bearing equipped wheels. **Maximum capacity is 150 pounds.**

Approximately: 5-1/16"L x 2-3/16"W



**No. 5003(BL) Live End Pulley**

1 - 6 lbs. 8 oz.

Plated steel construction equipped with 2 glass-filled nylon tired ball-bearing 5" diameter wheels. Attaches to track end. Extends beyond track 6".

Pulley width: Approximately 6-1/2".



**No. 5004(BL) Dead End Pulley**

1 - 2 lbs. 15 oz.

Plated steel construction equipped with 1 glass-filled nylon tired ball-bearing 5" diameter wheel. Attaches to track end.

Pulley width: Approximately 5".



**No. 5003-F Flying Live End Pulley**

1 - 5 lbs.

Used with flying type curtain machines. Routes operating cable 180 degrees up and over the track to the track mounted machine. Note: machine must be located at least 10' from the pulley.

Approximately: 8" long x 6" wide x 8" high.



**No. 5003-A Center Take-Off Live End Pulley**

1 - 5 lbs. 14 oz.

Routes operating cables perpendicular to the track. Add 1 each Model 5004 when using this device. 5003-A must be located a minimum of 4' from the end of the track. Additional pulleys may be required to mule operating lines to machine or floor pulley.

Approximately: 7-3/8" long x 6-1/2" wide x 2-3/8" high.



**No. 5008 Hanging Clamp**

1 - 1 lb. 4 oz.

Recommended spacing: 5' with additional units in curves and stack areas. Constructed of painted hardened steel. Pipe batten recommended for track suspension. Adjustable to any location.

Approximately: 4" high.



**No. 5023B(BL) Ceiling Clamp**

1 - 9.5 oz.

Recommended spacing: 5' with additional units at curves and in stack areas. Constructed of plated steel. For use with ceiling-mounted tracks. Approximately: 2-1/4" long x 1-1/4" wide x 1-3/4" high.